

S6-GR1P(2.5-6)K

Solis Single Phase Grid-Tied Inverters

Features:

- Max. efficiency 97.7%
- Wide voltage range and low startup voltage
- Supports export power control
- AFCI protection, proactively reduces fire risk
- 24-hour load consumption monitoring
- Adaptive weak grid

Models:

S6-GR1P2.5K / S6-GR1P3K

S6-GR1P3.6K / S6-GR1P4K

S6-GR1P4.6K / S6-GR1P5K

S6-GR1P6K



360° View

DATASHEET
S6-GR1P(2.5-6)K

Models	2.5K	3K	3.6K	4K	4.6K	5K	6K	
Input DC								
Recommended max. PV power	3.75 kW	4.5 kW	5.4 kW	6 kW	6.9 kW	7.5 kW	9 kW	
Max. input voltage	550 V	600 V						
Rated voltage	250 V	330 V						
Start-up voltage	60 V	120 V						
MPPT voltage range	50 - 450 V	90 - 520 V						
Max. input current				14 A / 14 A				
Max. short circuit current				22 A / 22 A				
MPPT number / Max. input strings number				2 / 2				
Output AC								
Rated output power	2.5 kW	3 kW	3.6 kW	4 kW	4.6 kW	5 kW	6 kW	
Max. apparent output power	2.8 kVA	3.3 kVA	4 kVA	4.4 kVA	5 kVA	5 kVA	6 kVA	
Max. output power	2.8 kW	3.3 kW	4 kW	4.4 kW	5 kW	5 kW	6 kW	
Rated grid voltage	1/N/PE, 220 V / 230 V							
Rated grid frequency	50 Hz / 60 Hz							
Rated grid output current	11.4 A / 10.9 A	13.6 A / 13.0 A	16.0 A / 15.7 A	18.2 A / 17.4 A	20.9 A / 20.0 A	22.7 A / 21.7 A	27.3 A	
Max. output current	13.3 A	15.7 A	16.0 A	21.0 A	23.8 A	25.0 A	27.3 A	
Power factor	> 0.99 (0.8 leading - 0.8 lagging)							
THDi	< 3%							
Efficiency								
Max. efficiency	97.3%	97.3%			97.6%	97.7%		
EU efficiency	96.5%	96.6%			97.1%	97.1%		
Protection								
DC reverse-polarity protection				Yes				
Short circuit protection				Yes				
Output over current protection				Yes				
Surge protection				Yes				
Grid monitoring				Yes				
Anti-islanding protection				Yes				
Temperature protection				Yes				
Multi peak scan				Yes				
Integrated AFCI				Yes ⁽¹⁾				
Integrated DC switch				Yes				
General Data								
Dimensions (W × H × D)	310 × 543 × 160 mm							
Weight	11 kg	11.2 kg			12 kg			
Topology	Transformerless							
Self-consumption (night)	< 1 W							
Operating ambient temperature range	-25 ~ +60°C							
Relative humidity	0 - 100%							
Ingress protection	IP66							
Noise emission (typical)	< 20 dB(A)							
Cooling concept	Natural cooling							
Max. operation altitude	4000 m							
Grid connection standard	G98 ⁽²⁾ or G99, VDE-AR-N 4105/VDE V 0124, EN 50549-1, VDE 0126/UTE C 15/VFR:2019, RD 1699/RD 244/UNE 206006/UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, EFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530, MEA, PEA							
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-3							
Features								
DC connection	MC4 connector							
AC connection	Quick connection plug							
Display	LCD							
Communication	RS485, Optional: Wi-Fi, GPRS							

(1) Activation required. (2) G98 for 2.5K-3.6K.